



# Product Information

## SHOWCASE

### Description

This product is a tough acrylic finish which is metal cross-linked for exceptional detergent resistance. It dries to a perfectly clear, hard film with high gloss. This finish is easy to apply, levels uniformly, and dries completely free of streaks and lap marks within 30 minutes. It can be recoated immediately, thus eliminating costly waiting or down time. This makes it ideal for schools, hospitals, nursing homes and other institutions, office buildings, industrial plants, retail stores and shopping malls.

The resistance of this finish to black marking is outstanding. In addition, it provides good slip resistance and freedom from powdering. Exceptionally scrubbable, this finish can be damp mopped or scrubbed without adversely affecting the hard, durable film. When needed, the finish may be maintained by spray buffing to restore and enhance it's original brilliance.

### Recommended Uses

This finish is recommended for finishing and maintaining asphalt tile, vinyl, vinyl composition, rubber, linoleum, seamless flooring, sealed wood, terrazzo, masonite and cork floors.

### Directions

1. Thoroughly clean the floor and remove all old wax or finish using a solution of a concentrated wax and finish stripper. Pay particular attention to corners and baseboards to ensure that all old coatings have been removed.
2. Scrub rinse well with clear water, pick up with a wet vac or mop and allow to dry.
3. Apply the finish using a rayon mop or gravity flow applicator.
4. For optimum gloss and durability apply 3 or 4 coats. Be sure previous coat has been dry (tack free) at least 15 minutes before applying next coat.
5. Maintain by damp mopping with a neutral cleaner.
6. Recoat traffic lanes on an as required basis.
7. Spray buffing with a material designed for this type maintenance will restore gloss.
8. For best results, dust daily with a properly treated mop.

**CAUTION:** Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally. FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN    KEEP FROM FREEZING    FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

### Specifications

Type product	Metal crosslinked acrylic
Appearance	Milky, white
Percent solids available @	16, 18, 25
pH (100%)	8.0 - 8.4
Weight per gallon	8.50, 8.54, 8.60 lbs.
Freeze/thaw stability	Passes 3 cycles
Leveling	Excellent
Recoatibility	Excellent
Gloss	Excellent
Buffability	Non-buffable
Heelmark resistance	Very good
Water resistance	Very good
Detergent resistance	Good
Powdering resistance	Excellent
V.O.C.	.228, 225, 226 gm/l
Coverage	1800 - 2000 sq. ft. per gallon