

# Product Information

## SUPER GLOSS DRESSING

### Description

Tile Star Super Gloss Dressing is a high solids specialized coating which will restore the brilliance of no-wax vinyl and urethane coated flooring. It dries to a perfectly clear, hard film with high gloss. This finish is easy to apply, levels uniformly, and dries completely free of streaks and lap marks within 30 minutes.

The resistance of this finish to black marking is outstanding. In addition, it provides good slip resistance and freedom from powdering. Exceptionally scrubbable, this finish can be damp mopped or scrubbed without adversely affecting the hard, durable film. Super Gloss Dressing will restore the shine on no-wax vinyl flooring in heavy traffic areas. Use a minimum of two coats for this procedure.

### WARNING: WET FLOORS ARE SLIPPERY.

Use proper caution anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

### Directions

**FLOOR PREPARATION:** Remove all old wax or finish. Rinse thoroughly with clear water and allow surface to dry.

**APPLICATION:** Apply with lamb's wool applicator or soft string mop. To assure highest gloss and to give maximum soil resistance, a second coat should be applied after the first coat has been dry for 30 minutes.

**MAINTENANCE:** Damp mop with a solution of Tile Star Neutral Cleaner. Never use an ammoniated cleaner as it may remove the finish. Recoat as necessary after mopping or scrubbing, but limit coats to five.

**CAUTION:** Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally.

**FIRST AID:** In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN      KEEP FROM FREEZING

### Specifications

Type product . . . . .	Metal crosslinked acrylic
pH . . . . .	8.0 - 8.4
Appearance . . . . .	Milky white
Percent solids . . . . .	18
Weight per gallon . . . . .	8.54 lbs.
Freeze/thaw stability . . . . .	Passes 3 cycles
Leveling . . . . .	Excellent
Recoatibility . . . . .	Excellent
Gloss . . . . .	Excellent
Buffability . . . . .	Nonbuffable
Heelmark resistance . . . . .	Very good
Water resistance . . . . .	Very good
Detergent resistance . . . . .	Good
Powdering resistance . . . . .	Excellent
Coverage . . . . .	1800 - 2000 sq. ft. per gallon