

Product Information

LATEX PRIMER

Description

Tile Star Latex Primer is a thick, heavy-duty, film forming agent used to prepare surfaces for the application of floor and wall coverings. It helps retard the migration of the adhesive into a porous subsurface. It is designed for use on drywall, plywood, hardboard, wood, plaster, concrete, old tile and old paint, and before the installation of no-wax tile, seamless flooring, wallpaper, plastic laminate, etc.

Directions

Clean the surface thoroughly to remove all old wax, grease, dirt and loose paint. Remove the gloss from old paint or other shiny surfaces by sanding.

Apply Primer with a brush or roller and allow to dry thoroughly before applying adhesive. Porous surfaces will require 2 coats of Primer

CAUTION: Contains polymer emulsions. Undiluted product may cause eye irritation. Avoid contact with eyes. Do not take internally.

FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING

Specifications

Type product	Latex primer
pH	9 ± 0.5
Appearance	Opaque white
Weight per gallon	8.42 lbs.
Freeze/thaw stability	Passes 3 cycles
Flash point	>210° F
Odor	Slight ammonia
Coverage	600 - 800 sq. ft. per gallon