



Product Information

MELT DOWN

Description

This product is an extra-heavy-duty stripper that provides outstanding stripping of today's floor finishes. This product makes the entire job easier since the chemical action substitutes for the physical and mechanical efforts previously used to remove old floor finish. It also eliminates the need for rinsing or neutralizing before applying floor finish. The technical aspects of this stripper, which contribute to its outstanding performance, are:

- **WETTING** - While some strippers possess strong surface tension, thereby causing puddling, this product wets the entire surface uniformly, producing total stripping.
- **PENETRATION** - While some strippers penetrate only part of the way into the floor finish, this product quickly and efficiently penetrates through the floor finish to release the bond to the floor.
- **EMULSIFICATION** - Unlike ordinary strippers, this product totally re-emulsifies multiple coats of aged floor finish, suspends the solids and allows complete removal with a mop or pickup vacuum.
- **COMPATIBILITY** - Realistically, not all of a wet film can be removed by any practiced technique. Since a limited residue will, therefore remain on the floor, it is critical this residue is compatible with the subsequent coats of finish. This product meets that criterion.

Simply mop the stripper on the floor and let stand for five minutes and vacuum up the liquified floor finish. There is no need to use floor machines or harsh stripping pads. This product will cut floor care costs substantially, saving time, manpower and equipment.

Recommended Uses

Use for removing floor finishes in facilities where conventional floor equipment is either unavailable, inappropriate or awkward to use. Ideal for vinyl, composition vinyl and masonry floors. Care should be exercised when being used on rubber or linoleum surfaces. Not recommended for asphalt tile surfaces.

Directions

NOTE: Test diluted product in an inconspicuous area to determine if floor surface is suitable for use of stripper. DO NOT USE ON ASPHALT TILE.

1. Depending on floor conditions, prepare stripping solution as follows:
 - a. For light buildup (2-3 coats) dilute 8 oz. (1 cup) stripper to one gallon of water.
 - b. For moderate buildup (4-7 coats) dilute 32 oz. (4 cups) stripper to one gallon of water.
 - c. For heavy buildup (8 or more coats) dilute 42 oz. (5½ cups) stripper to one gallon of water.
2. After determining the proper dilution, apply the stripping solution liberally and be certain surface is completely covered.
3. Allow stripper solution to remain on surface for 5 minutes or more. (Do not allow solution to dry on floor.)
4. Re-agitate the stripping solution on the floor with the same mop used for application.
5. For best results, pick up solution with a wet vacuum for complete removal of liquified floor finish.
6. Allow floor to dry completely before applying a finish.

ATTENTION: Avoid contact with glass. If this product is allowed to dry on glass, a residue will be created which may not be removable. If accidentally splashed on glass, flush immediately with water before the product dries.

WARNING

Causes serious eye irritation.

Causes skin irritation.

Wear protective gloves, and eye/face protection.

FIRST AID

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.


If eye irritation persists: Get medical attention.

IF ON SKIN: Wash with plenty of water. If skin irritation persists: Get medical attention.

Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Rinse mouth. Give large amounts of water or milk to drink. Do NOT induce vomiting. Call a physician.

KEEP OUT OF REACH OF CHILDREN FOR INDUSTRIAL & INSTITUTIONAL USE ONLY

 **WARNING:** This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

2/4/20

MELT DOWN

Specifications

Type	No scrub/no rinse stripper/degreaser
Weight per gallon	8.76 lbs.
Percent solids	11.8 ± 0.2
Percent active	28.5 ± 0.2
pH	12.9 ± 0.1
Appearance	Colorless
Viscosity	Less than A-1
Miscibility	In any proportion with water
Freeze/thaw stability	Passes three cycles
Flash point	None
Biodegradable	Yes
Phosphate	None
Butyl cellosolve	None
Coverage (32 oz./gal.)	1000 sq. ft. per gal.