

Product Information

POLISHED TILE SEAL

Description

Tile Star Polished Tile Seal represents a revolutionary concept in tile finishes for polished agglomerates, polished porcelain and high gloss marble. This blend of tough urethane resins and long wearing acrylic emulsions provides both the ease of application of conventional floor finishes and the durability of a urethane coating.

Tile Star Polished Tile Seal contains more solids than conventional floor finishes and has spray buff and burnish flexibility.

Recommended Uses

Polished Tile Seal is ideal for all forms of polished floors in industrial, commercial and institutional facilities. Its long wearing characteristics and economical coverage make it a prime candidate for use in schools, offices, hospitals, nursing homes, shopping centers, restaurants, retail stores.

NOTE: Do not use on any glazed tiles.

This product is also recommended for use on Saltillo (Mexican clay) tiles and other types of terra cotta tiles. For this use, three or more coats are recommended.

WARNING: WET FLOORS ARE SLIPPERY.

Use proper caution anytime floors are wet. This product is not recommended for exterior use or use on interior floors that are subject to standing water or wet conditions.

Directions - Delicate Surfaces

1. Strip the floor to remove all old wax and finish. If no wax or finish is present, use Tile Star Neutral Cleaner to wash completely.
2. Rinse well with clear water and let dry.
3. Apply Polished Tile Seal using a lamb's wool applicator or sponge mop. Apply at least 2 very light coats.
4. Allow each coat to dry 30 to 45 minutes under normal conditions, then recoat. Previous coat must be tack free before recoating.
5. Maintain by dust mopping daily. Wash as needed using Tile Star Neutral Cleaner.

WARNING



Causes serious eye irritation.

Wear eye protection. Wash contaminated body parts thoroughly after handling.

FIRST AID

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

Do not take internally.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING

Specifications

Type product Urethane fortified floor coating
pH 8 ± 0.5
Appearance Opaque white
Percent solids 20
Weight per gallon 8.6 lbs.
Freeze/thaw stability Passes 3 cycles
Viscosity (Gardner-Holdt tube) Less than A-1

Flash point None
Initial gloss (white vinyl, 60° meter) 88 - 90
Resistance to cold water Excellent
Resistance to abrasion Excellent
Drying time (normal conditions) 30 - 45 minutes
Washability Excellent
Coverage 2000 sq. ft. per gallon

8/20/20