

Product Information

INSTALLATION PRIMER

Description

Tile Star Installation Primer is a thick, heavy-duty, film forming agent used to prepare floor and wall surfaces for the application of tile mortar or adhesive. It encapsulates dust particles and is absorbed to create the most ideal bonding surface for adhesive. For use on concrete, plywood, luan or back board. A must for all self stick tile applications over raw plywood, dusty concrete or an existing tile floor.

Directions

Thoroughly clean and vacuum the surface to remove any dust and debris. For concrete, remove any wax, grease, dirt, or loose paint.

Apply Primer with a brush or roller and allow to dry thoroughly before applying adhesive. Porous surfaces will require 2 coats of Primer

Coverage: Approximately 150 - 200 sq. ft. per quart.

CAUTION: Contains polymer emulsions. Avoid contact with eyes. Do not take internally.

FIRST AID: In case of contact, flush eyes with plenty of water for 15 minutes. If irritation persists, see a doctor.

KEEP OUT OF REACH OF CHILDREN KEEP FROM FREEZING

Specifications

Type product	Latex primer
pH	9 ± 0.5
Appearance	Opaque white
Weight per gallon	8.42 lbs.
Freeze/thaw stability	Passes 3 cycles
Flash point	>210° F
Odor	Slight ammonia
Coverage	600 - 800 sq. ft. per gallon